

High cyclic density in rack format for critical sites with frequent grid outages.

The RFC12-180 is a 12 V, 180 Ah (10-hour rate) AGM Deep Cycle lead-acid battery from the Rekoser Front Terminal Deep Cycle series. It measures 560 × 126 × 316 mm and weighs 53 kg, with M8 terminals. It stores 2.16 kWh and delivers up to 1000 A. High cyclic density in rack format for critical sites with frequent grid outages. Typical applications: Telecommunications and Base Stations and Microgrids and Off-Grid Sites.

Formerly **RKC12-180FT**.

Nominal Voltage	12 V
Capacity (25°C)	180 Ah (C10)
Energy	2160 Wh
Weight	53 kg
Terminal	M8
Dimensions	560 × 126 × 316 mm

MAIN ADVANTAGES

- ✓ **Deep cycle:** Built for frequent cyclic discharge
- ✓ **Front terminal:** Rack integration with front access
- ✓ **Long life:** EUROBAT class above 12 years
- ✓ **AGM technology:** Sealed and maintenance-free

12
YEARS

LONG LIFE DESIGN

* EUROBAT CLASSIFICATION: >12 Years (Very Long Life).

2
YEARS

WARRANTY

* Subject to charge and temperature parameters stipulated in this datasheet.

MAIN APPLICATIONS



**TELECOMMUNICATIONS
AND BASE STATIONS**



**MICROGRIDS AND OFF-
GRID SITES**

QUALITY STANDARDS

CE CERTIFIED

ISO 9001 / 14001

IEC 60896-21/22

JIS C8704

GB/T19639

GRAPHICS (25°C)


Constant Discharge Ratings (A) at 25°C

F.V / Time	5MIN	10MIN	15MIN	30MIN	1HR	3HR	5HR	10HR	20HR
11.10 V	255A	217A	206A	147A	94.4A	44.4A	29.2A	17.4A	9A
10.80 V	298A	241A	226A	156A	97.2A	46.6A	30.6A	18A	9.54A
10.50 V	336A	265A	242A	164A	102A	47.5A	31A	18.4A	9.59A
10.20 V	387A	285A	260A	169A	104A	48.3A	31.4A	18.6A	9.72A
10.02 V	434A	314A	276A	176A	107A	48.8A	31.5A	18.8A	9.81A
9.60 V	486A	341A	293A	184A	109A	49.4A	32A	19.1A	9.9A


Constant Discharge Ratings (W) at 25°C

F.V / Time	5MIN	10MIN	15MIN	30MIN	1HR	3HR	5HR	10HR	20HR
11.10 V	480W	412W	393W	284W	183W	87.2W	57.7W	34.7W	18.1W
10.80 V	551W	452W	427W	298W	187W	90.7W	60.1W	35.8W	19.1W
10.50 V	615W	492W	453W	309W	194W	91.7W	60.3W	36.2W	19W
10.20 V	699W	523W	483W	317W	197W	92.3W	60.6W	36.4W	19.2W
10.02 V	773W	570W	507W	327W	200W	92.8W	60.3W	36.6W	19.2W
9.60 V	856W	612W	534W	340W	204W	93.3W	61W	36.9W	19.2W


CHARGE CHARACTERISTICS




DISCHARGE CHARACTERISTIC 25oC



SELF DISCHARGE CHARACTERISTICS



LIFE CHARACTERISTICS OF CYCLIC USE



SPECIFICATIONS

Nominal Voltage	12 V
Capacity (25°C)	180 Ah (C10)
Energy	2160 Wh
Cell number	6
Charge Voltage (25°C)	Cycle use: 14.6-14.8V (-30mV/C), max. Current 2.1A Float use: 13.6-13.8V (-20mV/C)
Max. Charge Current	45 A
Max. Discharge Current	1000 A
Internal Resistance	25 mΩ
Self Discharge	3 % of capacity per month at 20 °C
Capacity Affected by Temperature	40 °C: 102 %, 25 °C: 100 %, 0 °C: 85 %, -15 °C: 65 %

CONSTRUCTION

Component	Material
Container	ABS (Flame Retardant Optional)
Cover	ABS (Flame Retardant Optional)
Electrolyte	Sulphuric acid
Negative	Lead
Positive	Lead dioxide
Safety Valve	Rubber
Sealant	Epoxy Resin
Separator	Fibre Glass
Terminal	Copper

QUICK INSTALLATION GUIDE

To ensure optimal performance and maximize the lifespan of your **REKOSER RFC12-180** battery, follow these assembly and connection guidelines.

1. SPACE AND DIMENSION VERIFICATION

Before proceeding, ensure the receptacle or cabinet of your equipment complies with the unit's physical measurements:


Length: 560 mm

Width: 126 mm

Height: 316 mm

Total Height: 316 mm

Weight: 53 kg



2. TERMINAL CONFIGURATION (M8)

Terminals: Ensure your system's connectors match the M8 type to prevent electrical arcing.

Polarity: Check the positive and negative markings on the battery before connecting, to prevent short circuits.

3. CHARGE PARAMETERS

Cycle use: 14.6-14.8V (-30mV/C), max. Current 2.1A

Float use: 13.6-13.8V (-20mV/C)

Maximum Current: Do not exceed 45 A of charge.

4. SAFETY AND STORAGE

Maintenance: Sealed AGM technology, maintenance-free and leak-proof.

Cycling: Recharge fully after every discharge; never leave it discharged.

Position: Can be installed in any orientation, except inverted.

Storage: Store charged, in a cool and dry place, and recharge periodically.

NEARBY MODELS

RFC12-170 (12 V · 170 Ah) · **RFC12-200** (12 V · 200 Ah) · [See all RFC series models](#)

Specialized Technical Support
<https://rekoser.com> | +34 958 04 29 73