

Space optimisation and front-access connection for racks.

The RFT12-200 is a 12 V, 200 Ah (10-hour rate) AGM lead-acid battery from the Rekoser Front Terminal (AGM) series. It measures 522 × 238 × 218 mm and weighs 60 kg, with F12 terminals. It stores 2.4 kWh and delivers up to 1000 A. Space optimisation and front-access connection for racks. Typical applications: Telecommunications and Base Stations and UPS and Data Centers.

Formerly **RKE12-200FT**.

Nominal Voltage	12 V
Capacity (25°C)	200 Ah (C10)
Energy	2400 Wh
Weight	60 kg
Terminal	F12
Dimensions	522 × 238 × 218 mm

MAIN ADVANTAGES

- ✓ **Front terminal:** Connect and measure without removing the unit
- ✓ **19" rack:** Format designed for cabinets and racks
- ✓ **Long life:** EUROBAT class above 12 years
- ✓ **AGM technology:** Sealed and maintenance-free

12
YEARS

LONG LIFE DESIGN

* EUROBAT CLASSIFICATION: >12 Years (Very Long Life).

2
YEARS

WARRANTY

* Subject to charge and temperature parameters stipulated in this datasheet.

MAIN APPLICATIONS



**TELECOMMUNICATIONS
AND BASE STATIONS**



UPS AND DATA CENTERS

QUALITY STANDARDS

CE CERTIFIED

ISO 9001 / 14001

GB/T19639

IEC 61056

JIS C8702

GRAPHICS (25°C)

Constant Discharge Ratings (A) at 25°C

F.V / Time	5MIN	10MIN	15MIN	30MIN	1HR	3HR	5HR	10HR	20HR
11.10 V	299A	271A	249A	177A	115A	51.7A	34.6A	19.5A	10.3A
10.80 V	349A	301A	273A	187A	121A	53.4A	35.5A	20A	10.5A
10.50 V	395A	331A	293A	196A	125A	54.5A	36.4A	20.4A	10.7A
10.20 V	454A	356A	316A	203A	127A	55.3A	36.8A	20.7A	10.9A
10.02 V	509A	392A	334A	211A	130A	56A	37.1A	20.9A	11.2A
9.60 V	570A	425A	355A	221A	134A	56.7A	37.6A	21.2A	11.4A


Constant Discharge Ratings (W) at 25°C

F.V / Time	5MIN	10MIN	15MIN	30MIN	1HR	3HR	5HR	10HR	20HR
11.10 V	563W	514W	476W	340W	224W	91.3W	61.7W	35W	18.5W
10.80 V	646W	564W	517W	357W	232W	93.6W	62.7W	35.8W	18.9W
10.50 V	722W	614W	549W	370W	237W	94.6W	63.7W	36.2W	19.1W
10.20 V	820W	653W	585W	380W	240W	95.3W	64W	36.4W	19.3W
10.02 V	907W	711W	614W	392W	244W	95.8W	64.1W	36.6W	19.6VW
9.60 V	1004W	764W	647W	408W	249W	96.3W	64.5W	36.9W	19.9W


CHARGE CHARACTERISTICS




DISCHARGE CHARACTERISTIC 25oC



SELF DISCHARGE CHARACTERISTICS



FLOAT VOLTAGE VS FLOAT LIFE



SPECIFICATIONS

Nominal Voltage	12 V
Capacity (25°C)	200 Ah (C10), 210 Ah (C20)
Energy	2400 Wh
Cell number	6
Charge Voltage (25°C)	Cycle use: 14.6-14.8V (-30mV/C), max. Current 2.1A Float use: 13.6-13.8V (-20mV/C)
Max. Charge Current	60 A
Max. Discharge Current	1000 A
Internal Resistance	25 mΩ
Self Discharge	3 % of capacity per month at 25 °C
Capacity Affected by Temperature	40 °C: 102 %, 25 °C: 100 %, 0 °C: 85 %, -15 °C: 65 %

CONSTRUCTION

Component	Material
Container	ABS (Flame Retardant Optional)
Cover	ABS (Flame Retardant Optional)
Electrolyte	Sulphuric acid
Negative	Lead
Positive	Lead dioxide
Safety Valve	Rubber
Sealant	Epoxy Resin
Separator	Fibre Glass
Terminal	Copper

QUICK INSTALLATION GUIDE

To ensure optimal performance and maximize the lifespan of your **REKOSER RFT12-200** battery, follow these assembly and connection guidelines.

1. SPACE AND DIMENSION VERIFICATION

Before proceeding, ensure the receptacle or cabinet of your equipment complies with the unit's physical measurements:

Length: 522 mm

Width: 238 mm

Height: 218 mm

Total Height: 222 mm

Weight: 60 kg

2. TERMINAL CONFIGURATION (F12)

Terminals: Ensure your system's connectors match the F12 type to prevent electrical arcing.

Polarity: Check the positive and negative markings on the battery before connecting, to prevent short circuits.

3. CHARGE PARAMETERS

Cycle use: 14.6-14.8V (-30mV/C), max. Current 2.1A

Float use: 13.6-13.8V (-20mV/C)

Maximum Current: Do not exceed 60 A of charge.

4. SAFETY AND STORAGE

Maintenance: Sealed AGM technology, maintenance-free and leak-proof.

Position: Can be installed in any orientation, except inverted.

Storage: Store charged, in a cool and dry place, and recharge periodically.

NEARBY MODELS

RFT12-190 (12 V · 190 Ah) · [See all RFT series models](#)

The same battery in other series: **RHP12-200** (RHP Series – High Performance (AGM))

Specialized Technical Support
<https://rekoser.com> | +34 958 04 29 73