

The energy tank. 20+ years of proven service life.

The ROS12-50 is a 12 V, 50 Ah (10-hour rate) OPzS lead-acid battery from the Rekoser OPzS (Flooded) series. It measures 260 × 168 × 211 mm and weighs 20 kg, with F11 terminals. It stores 600 Wh and delivers up to 2500 A. The energy tank. 20+ years of proven service life. Typical applications: Solar/Wind Energy Systems, Electrical Substations, Telecommunications and Base Stations and Railway Signaling and Infrastructure.

Formerly **RKS12-50**.

Nominal Voltage	12 V
Capacity (25°C)	50 Ah (C10)
Energy	600 Wh
Weight	20 kg
Terminal	F11
Dimensions	260 × 168 × 211 mm

MAIN ADVANTAGES

- ✓ **Technology:** Vented tubular plates with liquid electrolyte
- ✓ **Maintenance:** Periodic topping up with distilled water required
- ✓ **Durability:** Over 20 years proven design life at 20°C
- ✓ **Control:** Transparent container for easy electrolyte level monitoring

20
YEARS

LONG LIFE DESIGN

* EUROBAT CLASSIFICATION: >12 Years (Very Long Life).

2
YEARS

WARRANTY

* Subject to charge and temperature parameters stipulated in this datasheet.

MAIN APPLICATIONS



SOLAR/WIND ENERGY SYSTEMS



ELECTRICAL SUBSTATIONS



TELECOMMUNICATIONS AND BASE STATIONS



RAILWAY SIGNALING AND INFRASTRUCTURE



MARITIME



UPS AND DATA CENTERS

QUALITY STANDARDS

CE CERTIFIED

ISO 9001 / 14001

IEC 60896-21/22

YD/T1360

BS6290 part 4

DIN40742

GRAPHICS (25°C)


Constant Discharge Ratings (A) at 25°C

F.V / Time	15MIN	30MIN	1HR	3HR	5HR	10HR	20HR
10.80 V	45.6A	36.6A	25.5A	12.4A	8.73A	5A	2.7A
10.50 V	48.1A	38A	26.3A	12.8A	9A	5.04A	2.72A
10.20 V	49.8A	39A	26.9A	12.8A	9.06A	5.07A	2.74A
9.90 V	51.7A	40.2A	27.6A	13A	9.19A	5.08A	2.74A
9.60 V	53A	41A	28A	13.1A	9.24A	5.09A	2.75A


Constant Discharge Ratings (W) at 25°C

F.V / Time	15MIN	30MIN	1HR	3HR	5HR	10HR	20HR
10.80 V	83.4W	68.5W	48.5W	24.2W	17.2W	10W	5.4W
10.50 V	88.1W	71.1W	50.1W	25W	17.7W	10W	5.44W
10.20 V	91.2W	72.8W	51.1W	25.2W	17.9W	10.1W	5.47W
9.90 V	94.7W	75.1W	52.4W	25.5W	18.1W	10.1W	5.49W
9.60 V	97W	76.7W	53.2W	25.7W	18.2W	10.1W	5.5W


CHARGE CHARACTERISTICS




DISCHARGE CHARACTERISTIC 25oC




SELF DISCHARGE CHARACTERISTICS



FLOAT VOLTAGE VS FLOAT LIFE



CYCLE DISCHARGE VOLTAGE CURVE (Test standard BS EN 61427:2005)



SPECIFICATIONS

Nominal Voltage	12 V
Capacity (25°C)	50 Ah (C10)
Energy	600 Wh
Cell number	6
Charge Voltage (25°C)	Cycle use: 14.1-14.4V (-5mV / o C/ cell) Float use: 13.2-13.5V (-3mV / o C/ cell)
Max. Charge Current	240 A
Max. Discharge Current	2500 A
Internal Resistance	0.35 mΩ
Self Discharge	3 % of capacity per month at 20 °C
Capacity Affected by Temperature	40 °C: 102 %, 25 °C: 100 %, 0 °C: 85 %, -15 °C: 65 %

CONSTRUCTION

Component	Material
Container	SAN
Cover	ABS (Flame Retardant Optional)
Electrolyte	Sulphuric acid
Negative	Lead
Positive	Lead dioxide
Safety Valve	Rubber
Sealant	Epoxy Resin
Separator	Fibre Glass
Terminal	Copper

QUICK INSTALLATION GUIDE

To ensure optimal performance and maximize the lifespan of your **REKOSER ROS12-50** battery, follow these assembly and connection guidelines.

1. SPACE AND DIMENSION VERIFICATION

Before proceeding, ensure the receptacle or cabinet of your equipment complies with the unit's physical measurements:


Length: 260 mm

Width: 168 mm

Height: 211 mm

Total Height: 826 mm

Weight: 20 kg



2. TERMINAL CONFIGURATION (F11)

Terminals: Ensure your system's connectors match the F11 type to prevent electrical arcing.

Polarity: Check the positive and negative markings on the battery before connecting, to prevent short circuits.

3. CHARGE PARAMETERS

Cycle use: 14.1-14.4V (-5mV / o C/ cell)

Float use: 13.2-13.5V (-3mV / o C/ cell)

Maximum Current: Do not exceed 240 A of charge.

4. SAFETY AND STORAGE

Maintenance: Check the electrolyte level and top up only with distilled or demineralised water.

Position: Always upright.

Ventilation: Install in a ventilated room: hydrogen is released during charging.

Storage: Store charged, in a cool and dry place, and recharge periodically.

NEARBY MODELS

ROS12-100 (12 V · 100 Ah) · [See all ROS series models](#)

Specialized Technical Support

<https://rekoser.com> | +34 958 04 29 73