

Maximum GEL longevity (2V). Deep-cycle endurance for critical infrastructure.

The RXG2-200 is a 2 V, 200 Ah (10-hour rate) GEL Deep Cycle lead-acid battery from the Rekoser eXtended Gel (2V) series. It measures 173 × 111 × 330 mm and weighs 13 kg, with F10 terminals. It stores 400 Wh and delivers up to 1000 A. Maximum GEL longevity (2V). Deep-cycle endurance for critical infrastructure. Typical applications: Solar/Wind Energy Systems, Electrical Substations, Telecommunications and Base Stations and UPS and Data Centers.

Formerly **RKG2-200**.



MAIN ADVANTAGES

- ✓ **Recovery:** Superior performance after deep discharges
- ✓ **Stable:** Low electrolyte stratification thanks to eXtended Gel technology
- ✓ **Longevity:** Excellent cyclic life in harsh conditions (Very Long Life >12 years design life)
- ✓ **Gel Tech:** Premium thixotropic gel electrolyte with high thermal stability

Nominal Voltage	2 V
Capacity (25°C)	200 Ah (C10)
Energy	400 Wh
Weight	13 kg
Terminal	F10
Dimensions	173 × 111 × 330 mm

15
YEARS

LONG LIFE DESIGN

* EUROBAT CLASSIFICATION: >12 Years (Very Long Life).

2
YEARS

WARRANTY

* Subject to charge and temperature parameters stipulated in this datasheet.

MAIN APPLICATIONS



SOLAR/WIND ENERGY SYSTEMS



ELECTRICAL SUBSTATIONS



TELECOMMUNICATIONS AND BASE STATIONS



UPS AND DATA CENTERS

QUALITY STANDARDS

CE CERTIFIED

ISO 9001 / 14001

IEC61427

IEC 60896-21/22

YD/T1360

BS6290 part 4

GRAPHICS (25°C)

Constant Discharge Ratings (A) at 25°C

F.V / Time	30MIN	1HR	3HR	5HR	10HR	20HR
1.80 V	161A	109A	49.5A	34.5A	20A	10.5A
1.75 V	167A	113A	51A	35.6A	20.1A	10.6A
1.70 V	171A	115A	51.4A	35.8A	20.3A	10.6A
1.65 V	176A	118A	51.7A	36.1A	20.3A	10.7A
1.60 V	180A	120A	52A	36.3A	20.4A	10.7A


Constant Discharge Ratings (W) at 25°C

F.V / Time	30MIN	1HR	3HR	5HR	10HR	20HR
1.80 V	301W	208W	97W	68W	39.8W	21W
1.75 V	312W	215W	100W	70.1W	40.1W	21.1W
1.70 V	320W	219W	101W	70.6W	40.3W	21.3W
1.65 V	330W	225W	101W	71.1W	40.4W	21.3W
1.60 V	337W	228W	102W	71.5W	40.5W	21.4W

CHARGE CHARACTERISTICS




DISCHARGE CHARACTERISTIC 25oC



SELF DISCHARGE CHARACTERISTICS



LIFE CHARACTERISTIC OF CYCLIC USE



SPECIFICATIONS

Nominal Voltage	2 V
Capacity (25°C)	200 Ah (C10)
Energy	400 Wh
Cell number	1
Charge Voltage (25°C)	Cycle use: 2.35-2.40V (-50mV/C), max. Current 2.1A Float use: 2.25-2.29V (-30mV/C)
Max. Charge Current	40 A
Max. Discharge Current	1000 A
Internal Resistance	25 mΩ
Self Discharge	3 % of capacity per month at 20 °C
Capacity Affected by Temperature	40 °C: 102 %, 25 °C: 100 %, 0 °C: 85 %, -15 °C: 65 %

CONSTRUCTION

Component	Material
Container	ABS (Flame Retardant Optional)
Cover	ABS (Flame Retardant Optional)
Electrolyte	Sulphuric acid
Negative	Lead
Positive	Lead dioxide
Safety Valve	Rubber
Sealant	Epoxy Resin
Separator	Fibre Glass
Terminal	Copper

QUICK INSTALLATION GUIDE

To ensure optimal performance and maximize the lifespan of your **REKOSER RXG2-200** battery, follow these assembly and connection guidelines.

1. SPACE AND DIMENSION VERIFICATION

Before proceeding, ensure the receptacle or cabinet of your equipment complies with the unit's physical measurements:


Length: 173 mm

Width: 111 mm

Height: 330 mm

Total Height: 364 mm

Weight: 13 kg



2. TERMINAL CONFIGURATION (F10)

Terminals: Ensure your system's connectors match the F10 type to prevent electrical arcing.

Polarity: Check the positive and negative markings on the battery before connecting, to prevent short circuits.

3. CHARGE PARAMETERS

Cycle use: 2.35-2.40V (-50mV/C), max. Current 2.1A

Float use: 2.25-2.29V (-30mV/C)

Maximum Current: Do not exceed 40 A of charge.

4. SAFETY AND STORAGE

Maintenance: Sealed gel battery, maintenance-free and leak-proof.

Charging: Keep to the stated charge voltage: gel is sensitive to overcharging.

Cycling: Recharge fully after every discharge; never leave it discharged.

Storage: Store charged, in a cool and dry place, and recharge periodically.

NEARBY MODELS

RXG2-150 (2 V · 150 Ah) · **RXG2-250** (2 V · 250 Ah) · [See all RXG series models](#)

Specialized Technical Support
<https://rekoser.com> | +34 958 04 29 73