

Maximum AGM longevity (2V). Critical infrastructure.

The RXL2-300 is a 2 V, 300 Ah (10-hour rate) AGM lead-acid battery from the Rekoser eXtended Long Life (AGM 2V) series. It measures 171 × 151 × 330 mm and weighs 18 kg, with F10 terminals. It stores 600 Wh and delivers up to 1500 A. Maximum AGM longevity (2V). Critical infrastructure. Typical applications: Railway Signaling and Infrastructure, Power Generation and UPS and Data Centers.

Formerly **RKE2-300**.

Nominal Voltage	2 V
Capacity (25°C)	300 Ah (C10)
Energy	600 Wh
Weight	18 kg
Terminal	F10
Dimensions	171 × 151 × 330 mm

MAIN ADVANTAGES

- ✓ **Format:** 2V single cells for modular configuration
- ✓ **Design Life:** 20 years ultra-long life
- ✓ **Construction:** Thick plates for extended service
- ✓ **Stability:** Excellent performance in floating use

15
YEARS

LONG LIFE DESIGN

* EUROBAT CLASSIFICATION: >12 Years (Very Long Life).

2
YEARS

WARRANTY

* Subject to charge and temperature parameters stipulated in this datasheet.

MAIN APPLICATIONS



**RAILWAY SIGNALING AND
INFRASTRUCTURE**



POWER GENERATION



UPS AND DATA CENTERS

QUALITY STANDARDS

CE CERTIFIED

ISO 9001 / 14001

GB/T19639

IEC 61056

JIS C8702

GRAPHICS (25°C)

Constant Discharge Ratings (A) at 25°C

F.V / Time	30MIN	1HR	3HR	5HR	10HR	20HR
1.80 V	241A	164A	74.2A	51.8A	30A	15.8A
1.75 V	250A	169A	76.5A	53.4A	30.2A	15.9A
1.70 V	257A	173A	77A	53.8A	30.4A	16A
1.65 V	265A	177A	77.6A	54.1A	30.5A	16A
1.60 V	270A	180A	78A	54.5A	30.5A	16A


Constant Discharge Ratings (W) at 25°C

F.V / Time	30MIN	1HR	3HR	5HR	10HR	20HR
1.80 V	451W	312W	145W	102W	59.7W	31.5W
1.75 V	468W	322W	150W	105W	60.1W	31.7W
1.70 V	480W	328W	151W	106W	60.5W	31.9W
1.65 V	495W	337W	152W	107W	60.7W	32W
1.60 V	505W	342W	153W	107W	60.8W	32.1W

CHARGE CHARACTERISTICS




DISCHARGE CHARACTERISTIC 25oC



SELF DISCHARGE CHARACTERISTICS



FLOAT VOLTAGE VS FLOAT LIFE



SPECIFICATIONS

Nominal Voltage	2 V
Capacity (25°C)	300 Ah (C10)
Energy	600 Wh
Cell number	1
Charge Voltage (25°C)	Cycle use: 2.35-2.40V (-3mV/C), max. Current 2.1A Float use: 2.25-2.29V (-2mV/C)
Max. Charge Current	60 A
Max. Discharge Current	1500 A
Internal Resistance	0.75 mΩ
Self Discharge	3 % of capacity per month at 25 °C
Capacity Affected by Temperature	40 °C: 102 %, 25 °C: 100 %, 0 °C: 85 %, -15 °C: 65 %

CONSTRUCTION

Component	Material
Container	ABS (Flame Retardant Optional)
Cover	ABS (Flame Retardant Optional)
Electrolyte	Sulphuric acid
Negative	Lead
Positive	Lead dioxide
Safety Valve	Rubber
Sealant	Epoxy Resin
Separator	Fibre Glass
Terminal	Copper

QUICK INSTALLATION GUIDE

To ensure optimal performance and maximize the lifespan of your **REKOSER RXL2-300** battery, follow these assembly and connection guidelines.

1. SPACE AND DIMENSION VERIFICATION

Before proceeding, ensure the receptacle or cabinet of your equipment complies with the unit's physical measurements:


Length: 171 mm

Width: 151 mm

Height: 330 mm

Total Height: 364 mm

Weight: 18 kg



2. TERMINAL CONFIGURATION (F10)

Terminals: Ensure your system's connectors match the F10 type to prevent electrical arcing.

Polarity: Check the positive and negative markings on the battery before connecting, to prevent short circuits.

3. CHARGE PARAMETERS

Cycle use: 2.35-2.40V (-3mV/C), max. Current 2.1A

Float use: 2.25-2.29V (-2mV/C)

Maximum Current: Do not exceed 60 A of charge.

4. SAFETY AND STORAGE

Maintenance: Sealed AGM technology, maintenance-free and leak-proof.

Position: Can be installed in any orientation, except inverted.

Storage: Store charged, in a cool and dry place, and recharge periodically.

NEARBY MODELS

RXL2-250 (2 V · 250 Ah) · **RXL2-350** (2 V · 350 Ah) · See all RXL series models

Specialized Technical Support
<https://rekoser.com> | +34 958 04 29 73